















Seattle Beyond


FIGURE: 1 Context Plan

























FIGURE: 3 Land Use


















LEGEND



MARINE HABITAT SUMMARY TABLE

COMMON NAME	SCIENTIFIC NAME	PRESENCE SOUTH OF FERRY TERMINAL IN +1.5 METERS TO MLLW	PRESENCE SOUTH OF FERRY TERMINAL IN 0 TO -10 METERS TO MLLW	PRESENCE NORTH OF FERRY TERMINAL IN +5 TO -10 METERS TO MLLW	PRESENCE BENEATH FERRY TERMINAL BELOW MLLW
Eelgrass					
Eelgrass	Zostera marina	None	None	None	None
Macroalgae					
Kelp	Laminaria Spp.	None	Few	Few	None
Popweed	Pylaiella littoralis	None	Common	None	None
Red weed	Agardhiella tenera	None	Few	None	None
Sea lettuce	Ulva Spp.	Common	Few	Common	Common
String acid hair	Desmarestia munda	None	Few	None	None
Macrofauna					
Anemones	Anthozoa Sp.	Common	Common	Common	Common
California sea cucumber	Parastichopus californicus	Few	Common	Common	Few
Coonstripe shrimp	Pandalus danae	Few	Common	None	None
Geoduck	Panopea abrupta	None	None	None	None
Horse clam	Tresus Spp.	Common	Common	Common	Common
Moon snail	Polinices lewisii	Few	Common	Common	Few
Nudibranch	Dendronotus Spp.	Common	None	Common	Few
Red rock crab	Cancer productus	Common	None	Common	Common
Rock borin piddock	Zirfaea pilsbryi	None	None	None	Common
Sea stars	Various species	None	None	None	Common

PRIORITY WILDLIFE SUMMARY TABLE

TRIORITI WILDLII E SOMMART TABLE				
SPECIES HABITAT	LOCATION FROM PROJECT			
Bald Eagle Nest	1.25 miles northeast (two nests), 2 miles north (1 nest)			
Heron Colony	1.3 miles north			
Osprey Nest	0.8 mile west			

FIGURE: 5 Existing Environmental Conditions
















A TOLL BOOTHS:

- Wood-framed, one-story buildings
- Limited future use because of programmatic and code



B BIKE BARN:

- Wood-framed, one-story building
- Limited future use because of programmatic and code requirements



C TERMINAL BUILDING:

- Concrete, two-story building
- Constructed in 1950
- Substantial alterations likely for change of use
- Substantial alterations likely to address seismic, mechanical, electrical, life safety and accessibility code requirements



OVERHEAD PEDESTRIAN WALKWAY:

- Heavy timber construction
- Constructed in 1972
- Selected structural members have been replaced
- Limited future use because of programmatic and code requirements



- Triangular shaped trestle of concrete construction

NORTH TRESTLE AND TRANSFER SPAN:

- Constructed in 1995
- Steel transfer span and towers refurbished



SOUTH OVERHEAD

- Steel construction
- Limited future use because of programmatic and code requirements



G PEDESTRIAN SHELTER:

- Steel construction



MAIN TRESTLE:

- Concrete construction
- Constructed in 1984



SOUTH TRESTLE AND TRANSFER SPAN:

- Concrete and steel construction
- Currently under construction and scheduled for completion in 2006



OTHER:

- Wood-framed, one-story buildings



FIGURE: 6 **Existing Building and Structure Survey**























FIGURE: 7
Existing Transportation









CIVIL

- Existing $4^{\prime\prime}$ Water Main in Olympic Drive serving the site from Winslow Way E.
- Existing gravity sanitary sewer lines flow to a sewer lift station and then pumped via force main to offsite sewer.
- Existing storm drainage system collects surface run-off and outfalls over the bluff toward Eagle Harbor at five locatons on site.
- Telephone enters the site off Winslow Way E. via underground and overhead lines.
- Natural gas lines are not on site per available as-built information.



















EXISTING ELECTRICAL SERVICE

- Puget Sound Energy (PSE) provides electrical service to the Bainbridge Island Ferry Terminal from overhead power lines on a power pole near the intersection between Winslow Way and Ferncliff Ave NE. The overhead power line routes south to a pole approximately 260 feet north of the Terminal Building on the west side of the roadway that leads to passenger drop-off area. From this pole, the power feed is routed underground to an electrical substation in the middle of the ferry terminal parking lot.
- A Puget Sound Energy transformer and the WSF Metering and Service disconnect Switchboard, SD-1 are located in the substation. The transformer changes the voltage from 12,470 volts to 480/277 volts. The secondary of the transformer is connected to the Switchboard SD-1.
- Switchboard SD-1 includes the PSE Revenue Meter, the main service disconnect circuit breaker and feeder breakers for site power distribution. The switchboard is rated 1,600 amperes at 480/277 volts. The trip rating on the main circuit breaker is 1,500 amperes.

STANDBY POWER

- Standby power is provided by engine generator, BG-1, located on the east end of the trestle between Slip 1 and Slip 2. The generator is rated 300KW at 0.8 power factor and is driven by a diesel engine. The engine generator package includes an 800-gallon sub-base fuel tank, which holds enough fuel for the generator to run at full load for 35 hours.
- BG-1 provides standby power to the Terminal Building, the Toll Booths, the Overhead Loading System and to each of the Slips (except for the shore power receptacles).



POWER AND COMM

POWER AND COMM





STANDBY GENERATOR BG-1

LEGEND

UNDERGROUND POWER
OVERHEAD POWER
EXPOSED POWER

UNDERGROUND COMMUNICATIONS

OVERHEAD COMMUNICATIONS

EXPOSED COMMUNICATIONS

NOTES:
UTILITY INFORMATION SHOWN ON SITE
WAS OBTAINED FROM WASHINGTON
STATE FERRIES PROVIDED BASEMAP AND
SUPPLEMENTED WITH FIELD INVESTIGATIONS
AND CITY OF BAINBRIDGE ISLAND UTILITY
INFORMATION: FIELD VERIFY EXISTING
UTILITIES PRIOR TO SITE DESIGN.

